

AQUAMARINE

The budget solution for up to 1.3"

Key Features:

- 1.3" (24mm) max. Sensor size
- 2 focal lengths: 28 mm and 35 mm
- Initial aperture: F2
- C-Mount and TFL-Mount available
- Ruggedized version and motorized iris available for 28 mm lens

Typical applications:

- Machine Vision
- AOI (Automated Optical Inspection)
- 3D and 2D measurement
- Traffic and surveillance

Name	Aperture	Focal length (mm)	Mount	Sensor size	Type	Size D x L (mm x mm)	Weight (g)	Filter thread	Code	Datasheet
AQUAMARINE 2.0/28 C	2.0-16	28	C	1.3" (24mm)	standard	34 x 38.3	78	M30.5 x 0.5	1001972	Download ↓
AQUAMARINE 2.0/28 C-R	2.0-16	28	C	1.3" (24mm)	ruggedized	34 x 38.3	78	M30.5 x 0.5	1062857	Download ↓
AQUAMARINE 2.0/28 C-MI	2.0-16	28	C	1.3" (24mm)	motorized iris	50 x 38.3	122	M30.5 x 0.5	1061456	Download ↓
AQUAMARINE 2.0/28 TFL	2.0-16	28	TFL	1.3" (24mm)	standard	34 x 38.3	85	M30.5 x 0.5	1098688	Download ↓
AQUAMARINE 2.0/35 C	2.0-16	35	C	1.3" (24mm)	standard	34 x 44.6	90	M30.5 x 0.5	1075451	Download ↓
AQUAMARINE 2.0/35 TFL	2.0-16	35	TFL	1.3" (24mm)	standard	34 x 44.6	90	M30.5 x 0.5	1098687	Download ↓