

TOPAZ

The specialists for long working distances

Key Features:

- 1.2" (19.3 mm) max. Sensor size (TOPAZ 2.4/6.5: 1.1")
- 6 focal lengths available: 6.5mm – 50mm
- Initial aperture: F2 – F2.8 | Motorized iris available
- C-Mount
- Optimized for long working distances up to infinity
- Low chief ray angle suitable for all SONY Pregius™ generations

Typical applications:

- Traffic
- Surveillance
- Long distance imaging

Name	Aperture	Focal length (mm)	Mount	Sensor size	Type	Size D x L (mm x mm)	Weight (g)	Filter thread	Code	Datasheet
TOPAZ 2.4/6.5 C	2.4–16	6.5	C	1.1" (17.6 mm)	standard	55 x 50.2	165	M82 x 0.75 *	1088899	Download ↓
TOPAZ 2.4/6.5 C-MI	2.4–16	6.5	C	1.1" (17.6mm)	motorized iris	55 x 50.2	225	M82 x 0.75 *	1100923	Download ↓
TOPAZ 2.8/12 C	2.8–22	12	C	1.2" (19.3mm)	standard	50 x 58	167	M62 x 0.75 *	1103137	Download ↓
TOPAZ 2.0/25 C	2.0–16	25	C	1.2" (19.3mm)	standard	34 x 40.2	86	M30.5 x 0.5	1081347	Download ↓
TOPAZ 2.0/25 C-MI	2.0–16	25	C	1.2" (19.3mm)	motorized iris	50 x 40.2	146	M30.5 x 0.5	1088585	Download ↓
TOPAZ 2.0/30 C	2.0–16	30	C	1.2" (19.3mm)	standard	34 x 40.5	87	M30.5 x 0.5	1078946	Download ↓
TOPAZ 2.0/30 C-MI	2.0–16	30	C	1.2" (19.3mm)	motorized iris	50 x 40.5	147	M30.5 x 0.5	1084646	Download ↓
TOPAZ 2.0/38 C	2.0–16	38	C	1.2" (19.3mm)	standard	34 x 48	133	M30.5 x 0.5	1076930	Download ↓
TOPAZ 2.0/38 C-MI	2.0–16	38	C	1.2" (19.3mm)	motorized iris	50 x 48	193	M30.5 x 0.5	1084666	Download ↓
TOPAZ 2.0/50 C	2.0–16	50	C	1.2" (19.3mm)	standard	34 x 56.6	156	M30.5 x 0.5	1079220	Download ↓
TOPAZ 2.0/50 C-MI	2.0–16	50	C	1.2" (19.3mm)	motorized iris	50 x 56.6	216	M30.5 x 0.5	1084649	Download ↓

*Optional filter adapter is required